

Models	Output BTUH*	Nozzle Size*	AFUE	Nom. Tons Cooling	Rated CFM**	Blower Size	Dimensions H x W x D (Inches)	Shipping Wt. (lbs)
HIGHBOY								
Oufa75-D3 Top Flue	58-74,000	.65GPH-80°B	83.0%	2-3	1412	10 x 8	54 x 19½ x 30⅝	225
Oufa95-D4 Top Flue	85-97,000	.75GPH-80°B	81.0%	2½-4	1756	10 x 10	54 x 19½ x 30⅝	225
Oufa125-D5 Top Flue	113-125,000	1.00GPH-80°B	81.0%	3-5	2204	12 x 9	54 x 22½ x 33⅝	275
LOWBOY								
Olfa95-D4 Front Flue	85-97,000	.75GPH-80°B	81.0%	2½-4	1760	10 x 9	37 x 19½ x 52⅝	250
Olra95-D4 Rear Flue	85-97,000	.75GPH-80°B	81.0%	2½-4	1760	12 x 10	37 x 19½ x 52⅝	250
Olfa125-D5 Front Flue	113-125,000	1.00GPH-80°B	81.0%	3-5	2160	12 x 10	37 x 22½ x 52⅝	285
Olra125-D5 Rear Flue	113-125,000	1.00GPH-80°B	81.0%	3-5	2221	12 x 10	37 x 22½ x 52⅝	285
Olra170-D5 Rear Flue	140-168,000	1.25GPH-80°B	80.0%	3½-5	2245	12 x 10	39 x 24 x 54¾	295
Olra200-BH Rear Flue	196,000	1.50GPH-80°B	80.0%	5-6	2660	12 x 12	42 x 26 x 61⅝	390
DOWNFLOW/HORIZONTAL								
Odha95-D3 Front Flue	85-97,000	.75GPH-80°B	81.0%	2-3	1410	10 x 10	59 x 20½ x 20½	225
Odha125-D5 Front Flue	113-125,000	1.00GPH-80°B	81.0%	3-5	2072	12 x 9	59 x 23½ x 20½	265
Ohha95-D3 Front Flue	85-97,000	.75GPH-80°B	81.0%	2-3	1487	10 x 10	59 x 20½ x 20½	225

*Determined by nozzle size. All units shipped with largest capacity nozzle

**CFM @ 0.2 Ext. Static Pressure—in W.C., at high blower speed

Flue size 6" diameter except OLRA200 at 8"
OHHA approved for horizontal installation only.