

RSG Series Commercial Split System A/C

Model	Cooling Cap. Nom. BTUH	Air Handler Model No.	EER	Power Supply	Dimensions H x W x D (inches)	Shipping Wt. (lbs)
RSG078A3	77,000/77,000	AHCG090A-Z*	11.2/11.2	208/230-3-60	32 ⁵³ / ₆₄ x 42 ⁴³ / ₆₄ x 31 ¹ / ₁₆	287
RSG078A4	77,000	AHCG090A-Z*	11.2	460-3-60	32 ⁵³ / ₆₄ x 42 ⁴³ / ₆₄ x 31 ¹ / ₁₆	287
RSG090A3	90,000/90,000	AHCG090A-Z*	11.2/11.2	208/230-3-60	32 ⁵³ / ₆₄ x 42 ⁴³ / ₆₄ x 31 ¹ / ₁₆	306
RSG090A4	90,000 92,000	AHCG090A-Z* AHCG120A-Z*	11.2 11.4	460-3-60	32 ⁵³ / ₆₄ x 42 ⁴³ / ₆₄ x 31 ¹ / ₁₆	306
RSG120A3	117,000/117,000	AHCG120A-Z*	11.2/11.2	208/230-3-60	44 ³ / ₄ x 62 ⁹ / ₆₄ x 39 ¹⁵ / ₁₆	541
RSG120A4	117,000	AHCG120A-Z*	11.2	460-3-60	44 ³ / ₄ x 62 ⁹ / ₆₄ x 39 ¹⁵ / ₁₆	541
RSG125A3	116,000/116,000	AHCG120A-Z*	11.2/11.2	208/230-3-60	44 ³ / ₄ x 62 ⁹ / ₆₄ x 39 ¹⁵ / ₁₆	626
RSG125A4	116,000	AHCG120A-Z*	11.2	460-3-60	44 ³ / ₄ x 62 ⁹ / ₆₄ x 39 ¹⁵ / ₁₆	626
RSG150A3	146,000/146,000	AHCG180A-Z*	11.1/11.1	208/230-3-60	44 ³ / ₄ x 73 ⁵⁷ / ₆₄ x 39 ¹⁵ / ₁₆	690
RSG150A4	146,000	AHCG180A-Z*	11.1	460-3-60	44 ³ / ₄ x 73 ⁵⁷ / ₆₄ x 39 ¹⁵ / ₁₆	690
RSG180A3	178,000/178,000	AHCG180A-Z*	11.0/11.0	208/230-3-60	44 ³ / ₄ x 88 ⁷ / ₈ x 39 ¹⁵ / ₁₆	786
RSG180A4	178,000	AHCG180A-Z*	11.0	460-3-60	44 ³ / ₄ x 88 ⁷ / ₈ x 39 ¹⁵ / ₁₆	786
RSG240A3	244,000/244,000	AHCG240A-Z*	10.0/10.0	208/230-3-60	44 ³ / ₄ x 88 ⁷ / ₈ x 39 ¹⁵ / ₁₆	992
RSG240A4	244,000	AHCG240A-Z*	10.0	460-3-60	44 ³ / ₄ x 88 ⁷ / ₈ x 39 ¹⁵ / ₁₆	992

* Select "L" or "K" Blower Drives—see AHCG commercial air handler spec sheet for blower selection criteria.