

Model	Ground Water—BTUH				Ground Loop—BTUH				Dimensions W x D x H (in.)	Shipping Wt. (lbs)
	Cooling @ 59° F EWT*	EER	Heating @ 50° F EWT*	COP	Cooling @ 77° F EWT*	EER	Heating @ 32° F EWT*	COP		
HPV018	20,600	24.2	17,200	4.4	18,400	16.3	13,900	3.4	22.4 x 22.4 x 40.5	173
HPV024	26,700	20.9	24,000	4.1	24,900	15.4	18,500	3.3	22.4 x 22.4 x 40.5	189
HPV030	31,700	20.1	29,600	4.1	28,900	15.1	23,400	3.4	22.4 x 22.4 x 40.5	197
HPV036	38,700	20.7	37,500	4.0	35,300	14.9	29,600	3.3	22.4 x 25.4 x 46.5	219
HPV042	45,900	19.6	44,000	3.8	40,500	14.4	34,300	3.3	22.4 x 25.4 x 46.5	234
HPV048	54,300	20.5	46,500	4.1	49,000	14.7	36,400	3.4	25.4 x 29.1 x 50.5	290
HPV060	66,600	19.9	60,000	3.9	60,100	14.8	47,500	3.3	25.4 x 29.1 x 50.5	305

**Power Supply: 208/230V-1-60**