

SPECIFICATIONS RSG14 Series Models

Model	Nom. Cap.BTUH	SEER*	Power (60 Hz)	Connection (In. ODS)		Line Size (in.)	Dimensions HxDxW (inches)	Shipping Weight
				Liquid	Suction			
RSG1418-1A	18,000	14	208-230/1	3/8	3/4	3/8-3/4	24 ¹ / ₄ x 27 ⁵ / ₈ x 27 ⁵ / ₈	141
RSG1424-1A	24,000	14	208-230/1	3/8	3/4	3/8-3/4	24 ¹ / ₄ x 27 ⁵ / ₈ x 27 ⁵ / ₈	174
RSG1430-1A	29,600	14	208-230/1	3/8	3/4	3/8-3/4	27 ³ / ₈ x 31 ⁵ / ₈ x 31 ⁵ / ₈	183
RSG1436-1A	34,600	14	208-230/1	3/8	7/8	3/8-7/8	35 ³ / ₈ x 31 ⁵ / ₈ x 31 ⁵ / ₈	222
RSG1442-1A	40,500	14	208-230/1	3/8	7/8	3/8-7/8	35 ³ / ₈ x 31 ⁵ / ₈ x 31 ⁵ / ₈	211
RSG1448-1A	47,000	14	208-230/1	3/8	7/8	3/8-1-1/8	35 ³ / ₈ x 31 ⁵ / ₈ x 31 ⁵ / ₈	246
RSG1460-1A	59,000	14	208-230/1	3/8	7/8	3/8 -1-1/8	35 ³ / ₈ x 31 ⁵ / ₈ x 31 ⁵ / ₈	260

Units come pre-charged with R-410A for a 15' line set.

Capacities will vary slightly depending on air handler and/or coil used with system.

Design, specifications and material subject to change without notice.

* SEER ratings with AHGV and HAGV variable speed air handlers range from 14.5 to 15.5, depending on model.



UNITS ARE CERTIFIED AND RATED UNDER AHRI STANDARD 210/240 FOR UNITARY AIR CONDITIONERS WHEN INSTALLED AS A MATCHED SYSTEM

