

# GTUV SERIES-UPFLOW-SPECIFICATIONS

MODEL NO.	GTUV45-E3B	GTUV60-E3B	GTUV75-E3B	GTUV75-E4B	GTUV90-E5B	GTUV105-E5B	GTUV120-E5B
High Fire Input BTUH	45,000	60,000	75,000	75,000	90,000	105,000	120,000
Low Fire Input BTUH	31,500	42,000	52,500	52,500	63,000	73,500	84,000
Heat Capacity BTUH	42,000	56,000	70,000	70,000	84,000	97,000	113,000
A.F.U.E.*	95%	95%	95%	95%	95%	95%	93.3%
Dimensions W x D All Models 34" H	17 <sup>1</sup> / <sub>2</sub> x 29 <sup>13</sup> / <sub>32</sub>	17 <sup>1</sup> / <sub>2</sub> x 29 <sup>13</sup> / <sub>32</sub>	17 <sup>1</sup> / <sub>2</sub> x 29 <sup>13</sup> / <sub>32</sub>	21 x 29 <sup>13</sup> / <sub>32</sub>	21 x 29 <sup>13</sup> / <sub>32</sub>	21 x 29 <sup>13</sup> / <sub>32</sub>	21 <sup>1</sup> / <sub>2</sub> x 29 <sup>13</sup> / <sub>32</sub>
Approx. Shipping Wt.	117 lbs.	123 lbs.	128 lbs.	139 lbs.	148 lbs.	150 lbs.	159 lbs.

