

GTUA 95% Gas Furnace Specifications

Model No.	High Fire Input BTH	Low Fire Input BTUH	Heating Cap. BUTH	Nom. Tons Cooling	Motor HP	AFUE*	Dimensions H x W x D (in.)	Shipping Wt. (lbs)
UPFLOW								
GTUA45-E3B	45,000	31,500	43,000	3	1/2	95.0%	34 x 17 ¹ / ₂ x 28 ¹³ / ₁₆	111
GTUA60-E3B	60,000	42,000	58,000	3	1/2	95.0%	34 x 17 ¹ / ₂ x 28 ¹³ / ₁₆	117
GTUA75-E3B	75,000	52,500	72,000	3	1/2	95.4%	34 x 17 ¹ / ₂ x 28 ¹³ / ₁₆	123
GTUA75-E4B	75,000	52,500	72,000	4	3/4	95.1%	34 x 21 x 28 ¹³ / ₁₆	145
GTUA90-E5B	90,000	63,000	87,000	5	3/4	95.0%	34 x 21 x 28 ¹³ / ₁₆	148
GTUA105-E5B	105,000	73,500	100,000	5	3/4	95.0%	34 x 21 x 28 ¹³ / ₁₆	152

Limited lifetime warranty on heat exchangers; limited 12 year warranty on all other components—see printed warranty for details of limitations.

**AFUE—Annual Fuel Utilization Efficiency*

These models are tax credit eligible. See your tax professional for how this may apply to you.